

CRYSTAL-RS

~5.1° spot beam. Assembly with holder.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 49.7 mm
Height	28.7 mm
Fastening	pin, screw
ROHS compliant	yes ⓘ




MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
CRYSTAL-RS	Single lens	PMMA	clear	
CRYSTAL-HLD	Holder	PC	white	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCN13552_CRYSTAL-RS	Single lens	288	64	32	0.0
» Box size:					





See also our general installation guide: www.ledil.com/installation_guide

PHOTOMETRIC DATA (MEASURED):


CREE

LED XHP35 HI
FWHM 5.7°
Efficiency 89 %
Peak intensity 48.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:




CREE

LED XHP50
FWHM 11.0°
Efficiency 93 %
Peak intensity 14.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:



CREE

LED XM-L
FWHM 7.0°
Efficiency 94 %
Peak intensity 34.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:




CREE

LED XP-G
FWHM 4.9°
Efficiency 89 %
Peak intensity 68.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:


PHOTOMETRIC DATA (MEASURED):





LED XP-L HD
FWHM 7.0°
Efficiency 88 %
Peak intensity 34.7 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LED XQ-E HI
FWHM 2.9°
Efficiency 88 %
Peak intensity 110.5 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON 3030 2D (Round LES)
FWHM 4.0°
Efficiency 94 %
Peak intensity 52.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON 5050 Round LES
FWHM 9.0°
Efficiency 94 %
Peak intensity 17.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LUMILEDS

LED LUXEON A
FWHM 5.1°
Efficiency 89 %
Peak intensity 58.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON Z ES
FWHM 3.0°
Efficiency 93 %
Peak intensity 103.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:





NICHIA

LED NV4x144A
FWHM 12.0°
Efficiency 92 %
Peak intensity 14.2 cd/Im
LEDs/each optic 1
Light colour White
Required components:



NICHIA



LED NVSW3x9A
FWHM 6.0°
Efficiency 89 %
Peak intensity 36.5 cd/Im
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):





LED NVSxx19B/NVSxx19C
 FWHM 5.3°
 Efficiency 89 %
 Peak intensity 42.5 cd/Im
 LEDs/each optic 1
 Light colour White
 Required components:



LED NWSx229A
 FWHM 8.0°
 Efficiency 92 %
 Peak intensity 27.9 cd/Im
 LEDs/each optic 1
 Light colour White
 Required components:



LED OSLOM SSL 150
 FWHM 3.0°
 Efficiency 94 %
 Peak intensity 108.9 cd/Im
 LEDs/each optic 1
 Light colour White
 Required components:




PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED LH351Z
FWHM 4.4°
Efficiency 90 %
Peak intensity 77 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED Z5M3
FWHM 6.0°
Efficiency 94 %
Peak intensity 3.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):






LED XHP70.2
FWHM 16.0°
Efficiency 95 %
Peak intensity 9 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-L HI
FWHM 5.6°
Efficiency 94 %
Peak intensity 70.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON Rubix
FWHM 10.0°
Efficiency 97 %
Peak intensity 26.8 cd/lm
LEDs/each optic 4
Light colour RGBW
Required components:




LED LUXEON Rubix
FWHM 4.0°
Efficiency 95 %
Peak intensity 106.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):





LED SBT-90
FWHM 8.0°
Efficiency 97 %
Peak intensity 33.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED OSTAR Projection Compact (Kx.CSLNM1.xx)
FWHM 4.0°
Efficiency 94 %
Peak intensity 139.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED SFH 4717AS
FWHM 6.7°
Efficiency 94 %
Peak intensity 46.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED SFH 4727AS
FWHM 6.7°
Efficiency 94 %
Peak intensity 47 cd/lm
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

[FCN13552_CRYSTAL-RS](#)