Technical Data Sheet LC ADAPTER DUPLEX SM APC LOW PROFILE GREEN/100 PAGE 1/1 ISSUE 04-06-13 SERIES LC PART NUMBER **F727754100** [0,866] 22 [0,669] (12 Ð 0,373 0,369 9,48 9,38 0,874 0,516 0,512 0,865 22,20 13,10 13,00 21,98 [0,709] PANEL PIERCING Ø2,40 or M2 18 7 0,516 28 0,71 0,70 18,10 G 0,394 0,374 9,50 Dimensions: mm [inches] **GENERAL Type:** IEC 61754-20 (LC) RJ-45 latching system Mounting: SC panel cut-out screw in (max. panel thickness 1.7mm) Alignement Sleeve: Zirconia Color: GREEN CHARACTERISTICS (Dependent on cable or fiber construction) Plastic molded : Material in accordance with **Material: TELCORDIA GR-326 CORE** flammability V0 (UL 94) Endurance: 200 matings **Mechanical:** Plug retention: 68N Storage temperature range: -40°C / +85°C Operating temperature range: -40°C / +70°C **Environmental:** Straight pull: 68 N **Proof test :** Side pull: 23 N

(Performance and specification: see document GEN_F727 001)

Vibration test: 10 to 55 Hz, 1,5 mm (peak to peak), 2 Hr/axis

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication ;, in the effort to improve our products, we reserve the right to make any changes judged necessary.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Radiall: F727754100