



SOLUTIONS

PRODUCTS AND SERVICES

SUPPORT

ABOUT US

Search Panduit.com

GO



Search within category

GO

BUY NOW

DESIGN / INSTALL

GCC6X6250-250



Grounding cross connector for #2 SOL – 250 kcmil (35 – 120mm²) wire size.

Specs

Packaging Details

Documents

★ Add to Favorites

🛒 Add to BOM

CSA Certified	Yes
UL Listed	Yes
BMEcat - Halogen Free	true
Color	Black
Copper Conductor Size Range (A)	#2 SOL - 250 kcmil
Copper Conductor Size Range (A) (mm ²)	(35 - 120)
Copper Conductor Size Range (B)	#2 SOL - 250 kcmil
Copper Conductor Size Range (B) (mm ²)	(35 - 120)
Ground Rod Size A (In.)	1/2 - 5/8
Ground Rod Size A (mm)	(12.7 - 15.9)
Ground Rod Size B (In.)	1/2 - 5/8
Ground Rod Size B (mm)	(12.7 - 15.9)
Height (mm)	53.8
Height - A	2.12
Height - B	2.12
Length (mm)	25.4
Length - A	1.00
Length - B	1.00
Material	Copper
Panduit Color Code	Black
Panduit Die Index No.	PG25
Part Features	Wide range-taking ability and multi-conductor (slotted) design allowing for conductor to conductor, conductor to rebar and conductor to ground rod.
Product Type	Cross Connector
Rebar Size A (In.)	3/8 - 1/2, #3 - #4
Rebar Size A (mm)	(9.5 - 12.7), (#10 - #13)
Rebar Size B (In.)	3/8 - 1/2, #3 - #4
Rebar Size B (mm)	(9.5 - 12.7), (#10 - #13)
Width (mm)	26.9
Width - A	1.06
Width - B	1.06

RoHS Compliancy Status

Compliant

Min. Order Qty.

1

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)