

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. INDUSTRIAL ETHERNET CATSE SHIELDED PATCH CORD (600V RATED) WITH RJ45 CONNECTIVITY TABLE 3 PANDUIT PART NUMBERS CONDUCTOR MIN. CABLE INSULATOR PART NUMBER LENGTH ISTPHCH0.3M** 0.3 METERS 4X TWISTED PAIR CONDUCTOR WIRE ISTPHCHO.6M** 0.6 METERS ISTPHCH1M** 1 METER FOAM TAPE ISTPHCH1.5M** 1.5 METER BRAID ISTPHCH2M** 2 METERS ISTPHCH2.5M** 2.5 METERS ISTPHCH3M** 3 METERS -FOIL SHIELD ISTPHCH3.5M** 3.5 METERS ISTPHCH4M** 4 METERS JACKET 4.5 METERS ISTPHCH4.5M** ISTPHCH5M** 5 METERS CROSS-SECTIONAL VIEW OF CABLE ISTPHCH7M** 7 METERS ISTPHCH10M** 10 METERS ISTPHCH15M** 15 METERS 20 METERS ISTPHCH20M** ISTPHCH25M** 25 METERS INDUSTRIAL ETHERNET CATSE SHIELDED PATCH CORD ISTPHCH40M** 40 METERS (600V RATED) WITH RJ45 CONNECTIVITY CUSTOMER DRAWING ITEM REVISION NAME 13M438AG/03 PANDUIT DATASET FILE NAME 13M438AG_DC02/03A MATERIAL: UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .x ± .1 [2.54] .xxx ± .005 [.127] .xx ± .01 [.25] ANGLES ± 5 ° DRAWING NUMBER: 06 10-11-17 JB0 NWW MARK SEE SHEET 1 FOR REVISION CONTROL 13M438AG-02 THIRD ANGLE 3M438AG-02 PROJECTION SCALE DRAWN BY DATE REV CHK APR DESCRIPTION ECN DATE ΒY BJN 1-16-14 DCS NONE SHT 2 OF 2 2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

ISTPHCH1MGY ISTPHCH1MBU