

AX104240-S1 Modular Connectors - Brilliance LC Connector OM1



For more Information
please call

1-800-Belden1

**General Description:**

FiberExpress Brilliance Field Installable Connector, LC, Multimode 62.5 μm , OM1, for 900 μm tight buffered fiber

Usage (Overall)

Suitable Applications:	Indoor termination of fiber cables: Patch panels, Communication outlets, Fiber-to-the-desk, Distribution frames, Campus, Customer premise, Access network, Data Centers, OM4 solutions
Related Parts:	FiberExpress Brilliance installation kits, Breakout kits

Physical Characteristics (Connectivity)**Dimensions**

Dimensions:

Height (in.)	Width (in.)	Length (in.)
0.395	0.232	1.594

Materials

Materials:

Description	Type	Material	Color
Connector Body	N/A	Plastic	Beige

Color

Color:	Beige
---------------	-------

Included Parts

Included Parts:	900 μm boot, dust cap
------------------------	----------------------------------

Packaging

Packaging:	Individually packaged in a plastic bag.
-------------------	---

Mechanical Characteristics (Connectivity)

Mechanical Specifications:

Parameters	Specifications
Interconnection Compatibility	compliant with TIA/EIA-604-10A (FOCIS 10)
Field Assembly Time	40 seconds
Durability (Multimode)	500 cycles, less than 0.2 dB change, FOTP-21
Durability (Single-mode)	500 cycles, less than 0.3 dB change, FOTP-21
Nominal Fiber OD	125 μm
Storage Temperature	-40°F to +140°F (-40°C to +60°C)
Operating Temperature	-40°F to +167°F (-40°C to +75°C)
Tensile strength on 2 mm Jacketed fiber	11.24 lb (5.1 Kg), less than 0.2 dB change, FOTP-6
Tensile strength on 900 μm tight buffered fiber	1.12 lb (0.5 Kg), less than 0.2 dB change, FOTP-6
Ferrule	Ceramic

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2006
MII Order #39 (China RoHS):	EUP 50
Telecommunications Standards:	TIA 568-C.3
Safety Listing:	ACA

Suitability

Suitability - Indoor:	Yes - Indoor
------------------------------	--------------

Transmission Characteristics (Connectivity)

Transmission Specifications:

Fiber type	Maximum Insertion Loss (Precision cleaver)	Typical Insertion Loss (Precision cleaver)	Maximum Insertion Loss (Field cleaver)	Typical Insertion Loss (Field cleaver)	Minimum reflectance
------------	--	--	--	--	---------------------

AX104240-S1 Modular Connectors - Brilliance LC Connector OM1

Multimode	0.50 dB	0.20 dB	0.75 dB	0.30 dB	-25 dB
Single-mode UPC	0.50 dB	0.30 dB	0.75 dB	0.30 dB	-50 dB
Single-mode APC	0.75 dB	0.30 dB	0.75 dB	0.30 dB	-60 dB

Notes (Overall)

Notes: Refer to Installation Guide PX105234 for installation procedures. Supplied with FiberExpress Brilliance installation kit.

Notes (Cont'd.):

Fiber can be reterminated up to 5 times with the same connector.

Product Family**Part Number List:**

Description	Belden Part Number
LC 62.5 µm Multimode OM1	AX104240-S1
LC 50 µm Multimode OM2	AX104241-S1
LC 50 µm Multimode OM3-4	AX104242-S1
LC, Singlemode OS2	AX104243-S1
LC 62.5 µm Multimode OM1, 25 per package	AX104240-B25
LC 50 µm Multimode OM2, 25 per package	AX104241-B25
LC 50 µm Multimode OM3-4, 25 per package	AX104242-B25
LC Singlemode OS2, 25 per package	AX104243-B25

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 1 Revision Date: 03-21-2012

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

[AX103151](#) [AX104268](#) [AX104272](#) [AX104273](#) [AX104274](#) [AX104278](#) [AX104280](#) [AX104281](#) [AX104282](#) [AX104285](#)
[AX104286](#) [AX104290](#) [AX104291](#) [AX104293](#) [AX104294](#) [AX203567](#) [AX203568](#)