Product datasheet Characteristics

XAPM14

empty control station - XAP-M - metal - without opening



Die-cast empty control station XAPM 80 x 80 mm
80 x 80 mm
74.5 mm
Undrilled
Blue
Blue
Zinc alloy
1 hole with blanking plug for cable gland with <= 14 mm 1 hole without blanking plug for cable gland with <= 14 mm
Flush mounting
IP69 conforming to NF C 20-010 IP65 conforming to IEC 60529 IP69K

Complementary

Product weight	0.61 kg
----------------	---------

Environment

Protective treatment	TC	_
Ambient air temperature for storage	-4070 °C	_:
Ambient air temperature for operation	-4070 °C	_
Electrical shock protection class	Class I conforming to IEC 60536 Class I conforming to NF C 20-030	


Contractual warranty

Warranty period	18 months

Product datasheet Dimensions Drawings

XAPM14

Dimensions and Fixing



- (1) (2) (3) 1 hole, without blanking plug, for cable gland with 14 mm/0.55 in. maximum clamping capacity
- 1 hole, with blanking plug (protrusion 6 mm/0.24 in.), for cable gland with 14 mm/0.55 in. maximum clamping capacity
- 2 x Ø 5.6 mm/0.22 in. holes, depth 20 mm/0.79 in.

a b		b		С		G		Н		P	
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
80	3.15	80	3.15	77	3.03	50	1.97	65	2.56	74.5	2.93