

Specification Sheet

Part Number: TSR2W-6A



One Piece Surface Raceway, 1-1/4", 6.0 ft Long, PVC, White, 120ft/Carton

Article Number	250-02603
Type	TSR2-6A
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none"><li>• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.</li><li>• PVC construction is lightweight, durable and more affordable than metallic raceway systems.</li><li>• Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing.</li><li>• Foam tape backing with rubber based adhesive conforms to any flat surface to assist with temporary positioning and mounting.</li><li>• Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.</li><li>• Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.</li></ul>
Quantity Per	carton

<b>Product Description</b>	HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations.
<b>Short Description</b>	One Piece Surface Raceway, 1-1/4", 6.0 ft Long, PVC, White, 120ft/Carton
<b>Global Part Name</b>	TSR2-6A-PVC-WH
<b>Length L (Imperial)</b>	6.0
<b>Length L (Metric)</b>	1.83
<b>Width W (Imperial)</b>	1.25
<b>Width W (Metric)</b>	31.75
<b>Height H (Imperial)</b>	.75
<b>Height H (Metric)</b>	19.05
<b>Material</b>	Polyvinylchloride (PVC)
<b>Material Shortcut</b>	PVC

<b>Flammability</b>	UL 94 V0
<b>Halogen Free</b>	No
<b>Operating Temperature</b>	+122°F (+50°C)
<b>Reach Compliant (Article 33)</b>	No
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	120
<b>Package Quantity (Metric)</b>	36.58
<b>Customs Number</b>	3925900000

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HellermannTyton:](#)

[TSR2W-6A](#)